

# SW24/4.0

## STRIP - STATIC WHITE



V/WATTS	RATED	CCT - LUMENS/CRI	<sup>3</sup> CONNECTOR/ WIRE IN	<sup>3</sup> CONNECTOR/ WIRE OUT	ILLUMINATED LENGTH (IN)		
<b>SW24/4.0</b> Voltage: 24 VDC Wattage: 4.0 W/Ft	<b>DRY</b>  <b>DMP</b>  <sup>4</sup> <b>ENC</b>  <b>WET</b>	<b>20</b> - 2000K 283/94 <b>24</b> - 2400K 306/95 <b>27</b> - 2700K 310/95 <b>30</b> - 3000K 328/96 <b>35</b> - 3500K 357/96 <b>40</b> - 4000K 369/96	<sup>1</sup> <b>BW</b> <b>BRL</b> <b>CLS</b>	<sup>1</sup> <b>BW</b> <b>BRL</b> <b>CLS</b>	<b>21"-288"</b> OR <sup>3</sup> <b>MATCH</b> 1" increments Matches EXT length ordered		
		<b>24</b> - 2400K 284/94 <b>27</b> - 2700K 276/97 <b>30</b> - 3000K ***/** <b>35</b> - 3500K ***/** <b>40</b> - 4000K 324/95			<sup>1</sup> <b>BW</b> <b>BRL</b>	<sup>1</sup> <b>BW</b> <b>BRL</b> <b>CLS</b>	<b>21"-180"</b> OR <sup>3</sup> <b>MATCH</b> 1" increments Matches EXT length ordered
		<b>20</b> - 2000K 260/94 <b>24</b> - 2400K 282/96 <b>27</b> - 2700K 285/95 <b>30</b> - 3000K 299/96 <b>35</b> - 3500K 323/96 <b>40</b> - 4000K 337/96			<sup>1</sup> <b>BW</b> <b>BRL</b>	<sup>1</sup> <b>BW</b> <b>BRL</b> <b>CLS</b>	<b>21"-288"</b> OR <sup>3</sup> <b>MATCH</b> 1" increments Matches EXT length ordered

ENC RATED STRIP ARE NOT FIELD CUTTABLE


- NOTES:**
- Field modifications must comply with Q-Tran's installation methods otherwise warranty is null and void
  - All data has +/- 5% tolerance
  - 5 year warranty
  - NRTL Listed for install in Storage Areas with Clothing, NEC Field 410.2 and 410.16 when assembled as a fixture, at Q-Tran facility (Not applicable for encapsulation)
- Custom Bare Wire length up to 120" - request different length by writing it in inches next to "BW" in the order code box
  - See resource guide for light loss factor
  - Wire orientation for MATCH will be dictated by extrusion Feed In/Feed Out selection
  - If ordering an encapsulated extrusion, ENC (Encapsulated in Extrusion) must be chosen for your strip

### TECHNICAL INFORMATION [L70 = 30000 HRS]

\*Tested with SW24/4.0-DRY

CCT	Lumen/ft	CRI Ra	CRI R9	TM30 Rf	TM30 Rg
2000K	283	94	64	86	107
2400K	306	95	97	94	103
2700K	310	95	95	93	102
3000K	328	96	96	93	101
3500K	357	96	92	91	100
4000K	369	96	90	90	101

### DIMENSIONS



Section (in)	DRY	DMP	WET
A	0.32"	0.32"	0.47"
B	0.16"	0.16"	0.16"
C	1.00"	1.00"	1.00"
D	0.06"	0.12"	0.21"

### CONNECTOR/WIRE IN

<sup>1</sup> <b>BW</b>	<b>BRL</b>	<b>CLS</b>
Bare Wire 24"	Male Barrel 6"	Not soldered DRY ONLY

### CONNECTOR/WIRE OUT

<sup>1</sup> <b>BW</b>	<b>BRL</b>	<b>CLS</b>
Bare Wire 24"	Female Barrel 6"	Not soldered

PROJECT NAME	DATE	COMPANY	TYPE	NOTE