



WURM-RGBW FIXTURES - FLEXIBLE (Q-CAP)



PRODUCT	MOUNTING	RATED	CCT	OUTPUT	LENS	TYPE	CONNECTOR/ WIRE IN	CONNECTOR/ WIRE OUT	END CAPS (NO FEED)	LENGTH (IN)
WURM-RGBW Voltage: 24 VDC Wattage: 1.5 W/Ft Per Channel 6.0 W/Ft Total Load	WSCS MCS	DRY WET	RGBW/27 RGBW/30	SO SO	ENC/CL ENC/CL	S1 P1	BW ¹BW	N/A ¹BW	WH N/A	4" increments from 4"-191" Tolerance +0.0"/-outpoint for installed product*

ENCAPSULATED PRODUCTS ARE NOT FIELD CUTTABLE

- NOTES:**
- Field modifications are not covered under Q-Tran warranty
 - Data subject to change, all data has +/- 5% tolerance
 - ¹ Custom Bare Wire length up to 120" - request different length by writing it in inches next to "BW" in the order code box


OUTPUT Tested for WURM-RGBW-WSCS-DRY

CCT	Lumen/ft	Wavelength	Circuit Wattage
Red	37	630	1.5
Green	124	513	1.5
Blue	32	466	1.5

CCT	Lumen/ft	CRI Ra	CRI R9	TM30 Rf	TM30 Rg	Circuit Wattage
2700K	89	93	67	92	100	1.5
3000K	99	94	75	91	102	1.5
All						6.0

LENS with LED visibility

ENC/CL




Encapsulated in Clear

NOTE: Indirect view recommended

CONNECTOR/WIRE IN


¹BW



Bare Wire 24"

CONNECTOR/WIRE OUT

¹BW



Bare Wire 24"

MOUNTING NOTE: 2 clips provided per first 12", 1 clip provided per additional foot

WSCS

White Snug Clip Small
QTY:


MCS

Magnetic Clip Small
(Cove use only)
QTY:

TYPE


SINGLE (Input only)

S1




PASS THROUGH (Input/Output)

P1




ORDER EXAMPLE



END CAPS (NO FEED)


WH



WHITE ENDCAPS
.13" added at end
.38" dim spot


END CAPS (WITH FEED)

End Feed
S1, P1




WHITE ENDCAPS
.13" added at end
.38" dim spot

FLEXIBILITY



Any Bend

DIMENSIONS



Profile
(Standard)

PROJECT NAME	DATE	COMPANY	TYPE	NOTE